



GROUT MAXIMUM 2 SECTIONS AT A TIME. USE INTERNAL VIBRATION FOR GROUT COMPACTION.

NOTES

- ASSUMPTIONS: (TO BE VERIFIED BY EOR)**
 DESIGN PER AASHTO LRFD 8th ED.
1. UNIT WEIGHT OF SOIL = 120 PCF
 2. BAR COVER AS SHOWN
 3. f'_c @ 28 DAYS = 4,500 PSI
 4. REINFORCEMENT = BAR PER ASTM A615, GRADE 60

			PREPARED FOR: UNIVERSAL PRECAST CONCRETE INC. 16538 CLEAR CREEK ROAD REDDING, CALIFORNIA	
			DATE: 9/24/19 SCALE: N.T.S.	SHEET TITLE: REINFORCING SUMMARY
			PROJECT: HOOVER DAM GATEWAY DECORATIVE FIGURE	
			CONTRACTOR: DELTA PROJ. NO.: 2019.525.002	DRWN BY: MPD CKD BY: RJA DWS. I.D. RS-01 SHT. NO.

REV. NO. DATE REVISION

PREPARED BY:

DELTA
 ENGINEERS, ARCHITECTS, & LAND SURVEYORS

860 HOOPER ROAD, ENDWELL NY 13760
 TEL: (607) 231-6600 FAX: (607) 231-6650